

KATO NK-250 E-v

Utriggere fullt utkjørt med frontjekk		- 360°					
Utriggere fullt utkjørt uten frontjekk		- over sider og hekk					
LØFTEKAPASITET (tonn)							
Aksjonsradius (m)	Bomlengde						
	19 m	13,5 m	17 m	20,5 m	24 m	27,5 m	31 m
2,5	25,00	17,50	14,50				
3,0	25,00	17,50	14,50	9,50			
3,5	25,00	17,50	14,50	9,50	7,50		
4,0	18,00	17,50	14,50	9,50	7,50	6,50	
4,5	16,30	15,80	14,50	9,50	7,50	6,50	6,00
5,0	14,85	14,40	13,25	9,50	7,50	6,50	6,00
5,5	13,65	13,25	12,20	9,50	7,50	6,50	6,00
6,0	12,30	12,20	11,30	9,50	7,50	6,50	6,00
6,5	11,20	11,00	10,50	9,50	7,50	6,50	6,00
7,0	10,25	10,11	9,80	8,80	7,50	6,50	6,00
7,5	9,40	9,20	9,10	8,30	7,50	6,50	6,00
8,0	8,65	8,45	8,35	7,80	7,00	6,10	5,65
8,3	8,25	8,05	7,95	7,50	6,75	5,90	5,45
9,0		7,20	7,10	6,95	6,25	5,45	5,05
9,5		6,65	6,50	6,55	5,90	5,20	4,80
10,0		6,00	5,90	6,20	5,60	4,95	4,60
11,0		5,00	4,85	5,25	5,00	4,50	4,20
11,8		4,30	4,20	4,60	4,65	4,15	3,95
12,0			4,10	4,45	4,60	4,10	3,90
14,0			2,90	3,25	3,40	3,50	3,35
15,3			2,30	2,70	2,85	3,00	3,00
16,0				2,40	2,60	2,75	2,85
18,0				1,75	1,95	2,10	2,15
18,8				1,50	1,75	1,90	1,95
20,0					1,45	1,60	1,70
22,0					1,10	1,20	1,30
22,3					1,00	1,15	1,25
24,0						0,90	0,95
25,8						0,65	0,75
28,0							0,50
29,3							0,40

Utriggere fullt utkjørt med frontjekk		- 360°					
Utriggere fullt utkjørt uten frontjekk		- over sider og hekk					
LØFTEKAPASITET (tonn)							
Bomvinkel (°)	31 m bom + 8 m jibb						
	Offset 5°		Offset 17°		Offset 30°		
	Aksjonsradius (m)	Kapasitet (tonn)	Aksjonsradius (m)	Kapasitet (tonn)	Aksjonsradius (m)	Kapasitet (tonn)	
80,0	7,7	2,75	9,1	1,95	10,4	1,35	
78,0	10,1	2,75	11,5	1,95	12,7	1,35	
75,0	10,5	2,75	12,1	1,88	13,5	1,35	
70,0	14,0	2,15	15,2	1,60	16,4	1,18	
65,0	17,2	1,78	18,2	1,35	19,3	1,04	
60,0	20,2	1,52	21,2	1,18	22,1	0,92	
53,0	23,8	1,28	24,8	1,00	25,7	0,80	
50,0	25,4	1,00	26,3	0,95	26,9	0,76	
48,0	26,3	0,85	27,2	0,82	28,0	0,72	
44,0	28,1	0,65	28,9	0,62	29,4	0,60	
39,4	30,0	0,48	30,6	0,45	31,2	0,45	

Utriggere delvis utkjørt uten frontjekk		- 360°					
Utriggere fullt utkjørt uten frontjekk		- over front					
LØFTEKAPASITET (tonn)							
Aksjonsradius (m)	Bomlengde						
	10 m	13,5 m	17 m	20,5 m	24 m	27,5 m	31 m
2,5	20,00	17,50	14,50				
3,0	20,00	17,50	14,50	9,50			
3,5	20,00	17,50	14,50	9,50	7,50		
4,0	16,50	17,50	14,50	9,50	7,50	6,50	
4,3	14,40	14,85	14,50	9,50	7,50	6,50	6,00
5,0	10,50	10,50	10,20	9,50	7,50	6,50	6,00
5,7	7,90	7,80	7,80	7,40	7,50	6,50	6,00
6,0	7,10	7,00	6,80	6,80	7,00	6,50	6,00
6,5	6,00	5,90	5,65	5,85	6,15	6,50	6,00
6,6	5,85	5,70	5,45	5,70	6,00	6,30	6,00
7,0	5,20	5,00	4,80	5,10	5,35	5,60	5,50
8,3	3,60	3,40	3,20	3,60	3,85	4,00	4,10
9,0		2,80	2,65	3,00	3,25	3,40	3,50
10,0		2,10	1,95	2,30	2,55	2,75	2,80
11,0		1,50	1,35	1,75	2,00	2,20	2,30
11,8		1,15	1,05	1,40	1,65	1,85	1,90
13,0			0,65	0,95	1,20	1,35	1,50
13,5			0,50	0,80	1,05	1,20	1,30
14,5				0,50	0,80	0,90	1,05
15,0					0,70	0,80	0,90
16,0					0,45	0,55	0,70
16,5						0,45	0,60
17,5							0,40

Utriggere delvis utkjørt uten frontjekk		- 360°					
Utriggere fullt utkjørt uten frontjekk		- over front					
LØFTEKAPASITET (tonn)							
Bomvinkel (°)	31 m bom + 8 m jibb						
	Offset 5°		Offset 17°		Offset 30°		
	Aksjonsradius (m)	Kapasitet (tonn)	Aksjonsradius (m)	Kapasitet (tonn)	Aksjonsradius (m)	Kapasitet (tonn)	
80,0	7,7	2,75	9,1	1,95	10,4	1,35	
78,0	10,1	2,75	11,5	1,95	12,7	1,35	
75,0	10,5	2,75	12,1	1,88	13,5	1,35	
72,0	12,5	1,90	14,0	1,60	15,0	1,25	
69,0	14,3	1,35	18,0	0,70	19,0	0,65	
65,0	16,7	0,80	18,0	0,70	19,0	0,65	
60,5	19,1	0,35	20,3	0,32	21,5	0,30	